

# DOUBLE INDUSTRY CO.,LTD

CHINESE SECURITY EQUIPMENT PROVIDER






4B'S BEST QUALITY







BEST PRICE






BEST DELIVERY

BEST WARRANTY



Item Photo	Description	Standard pack	G.W.kg	BATH/pc	Product Details
 <b>DB-20</b>	unlock time: 0.2s ; Pass capacity:40 person /min pass width: ≤500mm	machine core, main control board,s/s housing,bars with rotation plate; counter;Directi-on sign LED;	<b>110</b>	<b>55000</b>	size:1200*280*990mm; input voltage:220V,50HZ; operating temp:-30~+70; power:70w;input signals : keypad, bar code, magnetic stripe,token,proximity and smart card,Biometric identification readers etc;plus line: RS232:15m, RS485:1500m
 <b>DB-22</b>	unlock time: 0.2s ; Pass capacity:40 person /min pass width: ≤500mm	machine core, main control board,s/s housing,bars with rotation plate; counter;Directi-on sign LED;	<b>108</b>	<b>55000</b>	size:1240*280*980mm; input voltage:220V,50HZ; operating temp:-30~+70; power:70w;input signals : keypad, bar code, magnetic stripe,token,proximity and smart card,Biometric identification readers etc;plus line: RS232:15m,
 <b>DB-24</b>	unlock time: 0.2s ; Pass capacity:40 person /min pass width: ≤500mm	machine core, main control board,s/s housing,bars with rotation plate; counter;Directi-on sign LED;	<b>75</b>	<b>45000</b>	size:420*330*980mm; input voltage:220V,50HZ; operating temp:-30~+70; power:70w;input signals : keypad, bar code, magnetic stripe,token,proximity and smart card,Biometric identification readers etc;plus line: RS232:15m,
 <b>DB-25</b>	unlock time: 0.2s ; Pass capacity:40 person /min pass width: ≤500mm	machine core, main control board,s/s housing,bars with rotation plate; counter;Directi-on sign LED;	<b>110</b>	<b>65000</b>	size:1280*280*980mm; input voltage:220V,50HZ; operating temp:-30~+70; power:50w;input signals : keypad, bar code, magnetic stripe,token,proximity and smart card,Biometric identification readers etc;plus line: RS232:15m, RS485:1500m
 <b>DB-26</b>	unlock time: 0.2s ; Pass capacity:40 person /min pass width: ≤500mm	machine core, main control board,s/s housing,bars with rotation plate; counter;Directi-on sign LED;	<b>110</b>	<b>58000</b>	size:1280*280*980mm; input voltage:220V,50HZ; operating temp:-30~+70; power:50w;input signals : keypad, bar code, magnetic stripe,token,proximity and smart card,Biometric identification readers etc;plus line: RS232:15m, RS485:1500m; marble top

Item Photo	Description	Standard pack	G.W.kg	USD/pc	Product Details
 DB-2a	Pass capacity:40 person /min pass width: ≤600mm	s/s houing; plate bar; Direction sign;	25	18000	size:φ100×600×950mm; mechanical operation;
 DB-2b	unlock time: 0.2s ; Pass capacity:40 person /min pass width: ≤600mm	machine core, main control board,s/s housing,bars with rotation plate; counter;Directi -on sign;	35	55000	size:φ168X600X1015mm input voltage:220V,50HZ; operating temp:-30~+70; power:50w;input signals : keypad, bar code, magnetic stripe,token,proximity and smart card,Biometric identifi -cation readers etc;plus line: RS232:15m, RS485:1500m
 DB-241	open/close time:1.0s Pass capaci-ty:40person /min pass width: ≤700 mm;double-way control	machine core, main control board,s/s housing,plastic plate barrier; counter;Directi -on sign LED; (two pcs,one gate)	266	185000	size:1,200x320x1,000mm; input voltage:220V,50HZ; operating temp:-30~+70; power:70w;input signals : keypad, bar code, magnetic stripe,token,proximity and smart card,Biometric identifi -cation readers etc;plus line: RS232:15m, RS485:1500m
 DB-242	open/close time:1.0s Pass capaci-ty:40person /min pass width≤1200 mm;swing angle:0-180 /0-90degree	machine core, main control board,steel housing,plate barrier; counter;Directi -on sign LED; (two pcs,one gate)	268	175000	size:1200*280*990mm; input voltage:220V,50HZ; operating temp:-30~+70; power:50w;input signals : keypad, bar code, magnetic stripe,token,proximity and smart card,Biometric identifi -cation readers etc;plus line: RS232:15m, RS485:1500m
 DB-243	open/close time:1.0s Pass capaci-ty:40person /min pass width≤1200 mm;swing angle:0-180 /0-90degree	machine core, main control board,steel housing,plate barrier; counter;Directi -on sign LED; (two pcs,one gate)	278	165000	size:1400*300*990mm; input voltage:220V,50HZ; operating temp:-30~+70; power:50w;input signals : keypad, bar code, magnetic stripe,token,proximity and smart card,Biometric identifi -cation readers etc;plus line: RS232:15m, RS485:1500m
 DB-245	open/close time:1.0s Pass capaci-ty:40person /min pass width≤1200 mm;swing angle:0-180 /0-90degree	machine core, main control board,s/s housing,plate barrier; counter;Directi -on sign LED; (two pcs,one gate)	266	195000	size:1200*280*990mm; input voltage:220V,50HZ; operating temp:-30~+70; power:70w;input signals : keypad, bar code, magnetic stripe,token,proximity and smart card,Biometric identifi -cation readers etc;plus line: RS232:15m, RS485:1500m

Item Photo	Description	Standard pack	G.W.kg	USD/pc	Product Details
 <p><b>DB-2bb</b></p>	unlock time: 0.2s ; Pass capacity:40 person /min pass width: ≤600mm	machine core, main control board,s/s housing,swing plate; counter;Directi-on sign LED;	<b>110</b>	<b>65000</b>	size:φ168X600X1015mm input voltage:220V,50HZ; operating temp:-30~+70; power:50w;input signals : keypad, bar code, magnetic stripe,token,proximity and smart card,Biometric identification readers etc;plus line: RS232:15m, RS485:1500m
 <p><b>DB-S1</b></p>	open/close time:1.0s Pass capacity:40person /min pass width≤1200mm;double-way control	machine core, main control board,s/s housing,plastic plate barrier; counter;Directi-on sign LED;	<b>750</b>	<b>280000</b>	size:2360*1490*2310mm; input voltage:220V,50HZ; operating temp:-30~+70; power:50w;input signals : keypad, bar code, magnetic stripe,token,proximity and smart card,Biometric identification readers etc;plus line: RS232:15m, RS485:1500m
	unlock time: 0.2s ; running mode: two-ways run Pass capacity:40 person /min; pass width:	machine core, main control board,s/s housing, swing plate bar;		<b>59000</b>	size:φ168X1000mm(w)X1015mm(h) input voltage:220V,50HZ; operating temp:-30~+70; power:100w; input signals: keypad, bar code, magnetic stripe,token,proximity and smart card,Biometric identification readers etc;
					<b>MAGNETIC MACHINE</b>
					<b>NORMAL MACHINE</b>
